

# FITTINGS, COUPLINGS & CLAMPS



## TOPQUIK INDUSTRIAL SAFETY COUPLERS

- Prevents dangerous hose whip through 2-step disconnection
- Shock and crush resistant
- Non-marring body prevents scratching
- Super lightweight and ergonomic
- Maximum 225 PSI



## TOPRING

### 3/8" COUPLER

Model No.	Mfg. No.	NPT	Price/Each
<b>FEMALE THREAD</b>			
TLZ044	21.449	1/4	
TLZ045	21.469	3/8	
TLZ046	21.489	1/2	
<b>MALE THREAD</b>			
TLZ047	21.649	1/4	
TLZ048	21.669	3/8	
TLZ049	21.689	1/2	

### SAFETY COMES FROM 2-STEP DISCONNECTION:



- Slide the sleeve back to release downstream pressure
- The plug is released, but held within the coupler



- Slide the sleeve forward
- The plug is released completely



### 1/4" COUPLER

Model No.	Mfg. No.	NPT	SCFM	Price/Each
<b>FEMALE THREAD</b>				
TLZ040	20.449	1/4	36	
TLZ041	20.469	3/8	36	
<b>MALE THREAD</b>				
TLZ042	20.649	1/4	36	
TLZ043	20.669	3/8	36	

## QUICKSILVER 1/4" INDUSTRIAL HIGH PRESSURE COUPLERS

- Delivers high air volume with low pressure drop for better tool performance
- Corrosion resistant for long service life
- Drag guard protects against accidental disconnection
- Automatic push-to-connect operation
- Maximum 500 PSI
- 44 SCFM

Model No.	Mfg. No.	NPT	Price/Each
<b>FEMALE THREAD</b>			
BC080	20.446	1/4	
BC082	20.466	3/8	
<b>MALE THREAD</b>			
BC090	20.646	1/4	
BC093	20.666	3/8	



BC080

## TOPRING

## 1/4" INDUSTRIAL INTERCHANGE PLUGS

- Zinc Plated or Stainless Steel 304
- Corrosion resistant
- Made to precise standards to ensure fit

Model No.	Mfg. No.	NPT	Price/Each
<b>FEMALE THREAD</b>			
TA243	20.122	1/8	
TA244	20.142	1/4	
TLV344	20.146	1/4 (stainless)	
TA245	20.162	3/8	
<b>MALE THREAD</b>			
TA247	20.222	1/8	
TA248	20.242	1/4	
TLV345	20.248	1/4 (sealant)	
TA249	20.262	3/8	



TA243



TA247

## TOPRING

Model No.	Mfg. No.	I.D."	Price/Each
<b>HOSE BARB</b>			
TA252	20.342	1/4	
TA253	20.352	5/16	
TA254	20.362	3/8	


## AUTOMAX ARO 210 INTERCHANGE COUPLERS

- Accepts ARO 210 Plugs
- Automatic push to connect operation
- Deep knurled socket sleeve
- Max PSI: 250
- 34 SCFM

## TOPRING



TZ998



TS404

Model No.	Mfg. No.	NPT	Price/Each
<b>FEMALE THREAD</b>			
TZ998	23.444	1/4	
<b>MALE THREAD</b>			
TS399	23.644	1/4	

Model No.	Mfg. No.	I.D."	Price/Each
<b>HOSE BARB</b>			
TS404	23.744	1/4	
TS406	23.764	3/8	